

NEC MultiSync® LCD2190UXp Photo Edition



his new 21 inch monitor is an absolutely top class product with an array of technical characteristics and advanced features, which are unique as a whole, especially suited for graphics design, DTP, professional office applications, multi-media applications, etc. Moreover it offers excellent price/performance ratio.


- Bundle incl. display, SpectraView® Profiler Software 1.0 (Photo Edition) and sensor.
- High performance S-PVA TFT display
- Ultra-thin frame (15.7 mm)
- L-shape front button technology for intuitive OSD control
- ambix³™ Technology - safety of investment with analog/digital interfaces (DVI-I, DVI-D, VGA) with up to 3 inputs simultaneously

see more.

NEC Display Solutions

[illegible]

Panel Technology	S-PVA TFT
Screen Size [inch/cm]	21.3 / 54
Pixel Pitch [mm]	0.270
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Contrast Ratio (typ.)	1000:1
Brightness (typ.) [cd/m²]	300
Response Time (typ.) [ms]	8 (grey-to-grey), 16 (9 white / black; 7 black / white)
Colours [Mio.]	16.77
Horizontal Frequency [kHz]	31.5 - 91.1
Vertical Frequency [Hz]	50.0 - 85.0
Optimum Resolution	1600 x 1200 at 60 Hz
Supported Resolutions	1280 x 1024; 1280 x 960; 1200 x 1600; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Connectors	Digital: 1 x DVI-D; Digital/ Analog: 1 x DVI-I; Analog: 1 x D-sub 15 pin
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Adjust Functions	Advanced NTAA (Advanced Non-Touch-Auto-Adjustment); Advanced User Menu; Auto Adjust; Black Level; Brightness; Colour Temperature Control; Contrast; Expansion Mode; Fine Adjust (analog); Hotkeys; Intelligent Power Management; Language Select; Monitor Information; OmniColor™: sRGB and 6-axis-colour-control; On-Screen-Display (OSD) lock-out; Sharpness; User Menu
Safety and Ergonomics	CE; TCO 03; TÜV Ergonomics; TÜV GS; C-tick; GEEA/Energy Label; Energy Star; FCC Class B; PCT/ Gost; UL/C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; PCBC/B-mark; PSB; RoHS
Power Consumption on Mode [W]	60 (max.)
Power Consumption Power-Saving Mode [W]	1
Power Supply	100-120 V/220-240 V; 0.74 A/0.32 A; internal power supply
Ambient Temperature (operating) [°C]	+5 to +35
Ambient Humidity (operating) [%]	30 to 80
VESA Mounting [mm]	100 x 100
ErgoDesign®: Height adjustable Stand [mm]	150
Screen Tilt / Swivel [°]	-5 to +30 / -170 to +170
Dimensions (W x H x D) [mm]	464.8 x 424.8 - 574.8 x 247.3 (Landscape mode)
Bezel Width [mm]	15.7 (left and right)
Weight [kg]	10.7
Cable Management	yes
Kensington Lock	yes
Benefits	Adjustable power LED (colour and brightness); Advanced NTAA (Advanced Non-Touch- Auto-Adjustment); AmbiBright; ambix ^{3TM} ; Auto Black Level; Auto Brightness; Auto Contrast; AutoBright; CableComp with Sync Continuity Detection; ColorComp; DDC/CI compatible; Direct Brightness and Contrast; EcoModes; NaViSet® and NaViSet® Administrator compatible; OmniColor™: sRGB and 6-Axis-Colour-Control; Overdrive; Quick release Stand and Handle; Rapid Response Technology; RapidMotion; Real Time Clock with Scheduler (Power-On and Power-Off Timer); Self Diagnostics; TORO™ Design
Audio Functions	Option: MultiSync® Soundbar 90
Colour Versions	Black Front Bezel, Black Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable DVI-D - DVI-D; Signal Cable DVI-A - VGA; CD-ROM; Sales Office List; User Manual
Warranty	3 years warranty incl. backlight



NEC Display Solutions Europe GmbH