

Lenovo ThinkVision LT1953 Specifications

Product Specifications Reference (PSREF)

Name Case color Type-model Panel Viewable image size Max view area (W x H) Optimum resolution Max pixel rate Aspect ratio Pixel pitch (mm) Dot/Pixel per Inch Brightness Contrast ratio Pixel response time Color gamut Viewing angle at 10:1 CR Stand Bezel width Dimensions (HxWxD, excluding stand) Dimensions (HxWxD, including stand) Power supply Weight Limited warranty⁴ Available date		LT1953 Wide Flat Panel Monitor Business black 1453-HB1 (Latin America) TFT-LCD, twisted nematic (TN), White LED backlight 19" (482.6mm) diagonal 16.07" x 10.05" (408.2mm x 255.2mm) 1440x900 205MHz(VGA), 165MHz(DVI) 16:10 0.2835mm 89.4 dpi 250 nits or cd/m² (typical) 1000:1 (typical) 5ms (typical) 72% 170° horizontal, 160° vertical Tilt stand Sides: 0.66" (16.8mm); top: 0.66" (16.8mm); bottom: 0.66" (16.8mm) 11.42" H x 17.45" W x 1.99" D; 290.2mm H x 443.2mm W x 50.5mm D 13.94" H x 17.45" W x 6.33" D; 354.0mm H x 443.2mm W x 160.7mm D 17 watts typical, 20 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) 6.61 lb; 3.00kg 3 year (includes backlight) March 2013	Features • Widescreen 19-inch monitor • Supports 1440x900 resolution • VGA and DVI connections • Arsenic free glass • Support Lenovo Tiny PC via VESA mount • 85% PCC plastic resins • Microsoft® Windows® 7 certified • Microsoft Windows 8 certified
VESA-compliant² Power management Ergonomics Emission standards Environmental Preset resolutions Presets / user settings		VESA DDC2B/CI ENERGY STAR® 6.0 ISO 9241-307 MPR-2, FCC Class B TCO Displays 6.0, TCO Certified Edge 1.1, WEEE, RoHS, EPEAT™ Gold rating, ULE Gold VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA+: 1440x900 Standard presets: 20; user settings: 20	 ThinkVision LT1953 Wide Monitor
Viewing adjustments Rotating screen On screen display Control features Multiple input Monitor connectors Signal cables Mounting features Security		Tilt: 22° back, -5° forward None On screen display with digital user controls (8 languages) Direct access (buttons on front) for automatic image setup, input switch, and brightness Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)	
Ship group		Monitor, tilt stand, Setup poster, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter black power cord	

Limited Warranty ⇒ 3 year limited warranty⁴ ⇒ International Warranty Service⁵ ⇒ Replacement normally arrives in two business days, excluding holidays ⇒ Lenovo pays all shipping costs for valid warranty claims⁶ ⇒ Service upgrade options:⁷ • 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209) • 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233) • 4 year, mail exchange (51J0589) • 5 year, mail exchange (51J0590) ⇒ 24x7⁸ day toll-free support for warranty issues during the warranty period⁴	Accessories Kensington MicroSaver Cable Lock 73P2582 Kensington Twin Head Cable Lock 45K1620 Lenovo Security Cable Lock 57Y4303 See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision
---	--

See footnotes for important warranty information
Latin America model announced March 5, 2013 (This model is not available in the US)

© Lenovo
(LT1953) March 2013